



Safety Data Sheet

Butyl glycol

Revision 4, 14/02/2023

1. IDENTIFICATION

Product Name	Butyl glycol
Other Names	2-Butoxyethanol; Butyl cellosolve; Butyl glycol; Butyl glycol ether; EGBE; Ethylene glycol, mono-n-butyl ester; Glycol Ether EB
Uses	Solvent; Chemical intermediate.
Chemical Family	No Data Available
Chemical Formula	C ₆ H ₁₄ O ₂
Chemical Name	Ethanol, 2-butoxy-
Product Description	No Data Available

Contact Details of the Supplier of this Safety Data Sheet

Organisation	Location	Telephone
Aurora Cleaning Supplies	F1 / 5 Bungaleen Court Dandenong South VIC 3175	03 9768 2669

Emergency Contact Details

For emergencies only; DO NOT contact these companies for general product advice.

Organisation	Location	Telephone
Chemcall	Australia	1800-127406 +64-4-9179888
Chemcall	Malaysia	+64-4-9179888
Chemcall	New Zealand	0800-243622 +64-4-9179888
National Poisons Centre	New Zealand	0800-764766
CHEMTREC	USA & Canada	1-800-424-9300 CN723420 +1-703-527-3887

2. HAZARD IDENTIFICATION

Poisons Schedule (Aust) Schedule 6

Globally Harmonised System

Safety Data Sheet, Butyl glycol, Revision 4, 14/02/2023

Hazard Classification	Hazardous according to the criteria of the Globally Harmonised System of Classification and Labelling of Chemicals (GHS)
Hazard Categories	Flammable Liquids - Category 4 Acute Toxicity (Oral) - Category 4 Acute Toxicity (Dermal) - Category 4 Acute Toxicity (Inhalation) - Category 4 Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Irritation - Category 2A Specific Target Organ Toxicity (Single Exposure) - Category 3

Pictograms



Signal Word Warning

Hazard Statements	H227	Combustible liquid.
	H302 + H312 + H332	Harmful if swallowed, in contact with skin or if inhaled.
	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
	H335	May cause respiratory irritation.

Precautionary Statements	Prevention	P210	Keep away from flames and hot surfaces. No smoking.
		P280	Wear protective gloves/eye protection/face protection.
		P261	Avoid breathing mist/vapours/spray.
		P270	Do not eat, drink or smoke when using this product.
		P271	Use only outdoors or in a well-ventilated area.
		P233	Keep container tightly closed.
	Response	P370 + P378	In case of fire: Use carbon dioxide (CO ₂), dry chemical, regular foam extinguishing agent or water spray for extinction.
		P312	Call a POISON CENTER or doctor if you feel unwell.
		P302 + P352	IF ON SKIN: Wash with plenty of water/...
		P337 + P313	If eye irritation persists: Get medical advice/attention.
		P330	Rinse mouth.
		P304 + P340	IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
		P332 + P313	If skin irritation occurs: Get medical advice/attention.
	Storage	P362	Take off contaminated clothing.
		P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403 + P235		Store in a well-ventilated place. Keep cool.	
Disposal	P405	Store locked up.	
	P501	Dispose of contents/container in accordance with local / regional / national / international regulations.	

National Transport Commission (Australia)

Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)

Dangerous Goods Classification NOT Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)

Environmental Protection Authority (New Zealand)

Hazardous Substances and New Organisms Amendment Act 2015

HSNO Classifications	Physical Hazards	3.1D	Flammable liquid - low hazard
	Health Hazards	6.1D	Substances that are acutely toxic - Harmful
		6.4A	Substances that are irritating to the eye

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Chemical Entity	Formula	CAS Number	Proportion
2-Butoxyethanol	C6H14O2	111-76-2	<=100 %

4. FIRST AID MEASURES

Description of necessary measures according to routes of exposure

Swallowed	IF SWALLOWED: Rinse mouth, then give 1 cup (240 ml) of water. Do not induce vomiting. Immediately call a Poison Centre or doctor/physician for advice. Never give anything by mouth to an unconscious person.
Eye	IF IN EYES: Immediately flush eyes with running water for several minutes, holding eyelids open and occasionally lifting the upper and lower lids. Remove contact lenses if present and easy to do. Continue rinsing for at least 15 minutes. If eye irritation persists, get medical advice/attention, preferably from an ophthalmologist. *Protect unharmed eye.
Skin	IF ON SKIN: Remove contaminated clothing and shoes immediately. Flush skin with running water for at least 15 minutes. Call a Poison Centre or doctor/physician for advice. Wash contaminated clothing and shoes before reuse. *If burn is present, treat as any thermal burn, after decontamination.
Inhaled	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a Poison Centre or doctor/physician for advice. Apply resuscitation if victim is not breathing - Administer oxygen if breathing is difficult.
Advice to Doctor	Treat symptomatically. Ensure that attending medical personnel are aware of the identity and nature of the product(s) involved, and take precautions to protect themselves. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. In cases where several ounces (60 - 100 ml) have been ingested, consider the use of ethanol and hemodialysis in the treatment. If ethanol is used, a therapeutically effective blood concentration in the range of 100 - 150 mg/dl may be achieved by a rapid loading dose followed by a continuous intravenous infusion. 4-Methyl pyrazole (Antizol®) is an effective blocker of alcohol dehydrogenase and should be used in the treatment of ethylene glycol butyl ether (EGBE) or methanol intoxication, if available. The signs and symptoms of poisoning include anion gap metabolic acidosis, CNS depression, renal tubular injury, and possible late stage cranial nerve involvement. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Maintain adequate ventilation and oxygenation of the patient. In severe poisoning, respiratory support with mechanical ventilation and positive end expiratory pressure may be required. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
Medical Conditions Aggravated by Exposure	No information available.

5. FIRE FIGHTING MEASURES

General Measures	Keep people away. Isolate fire and deny unnecessary entry. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. If safe to do so, move undamaged containers from fire area. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.
Flammability Conditions	Combustible liquid; May burn but does not ignite readily.
Extinguishing Media	Use dry chemical, Carbon dioxide (CO ₂), foam or water spray for extinction. Burning liquids may be extinguished by dilution with water - Do not use direct water stream. May spread fire. *Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams

may function, but will be less effective.

Fire and Explosion Hazard	Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.
Hazardous Products of Combustion	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include Carbon oxides.
Special Fire Fighting Instructions	Contain runoff from fire control or dilution water - Runoff may pollute waterways.
Personal Protective Equipment	Wear self-contained breathing apparatus (SCBA) and chemical splash suit. SCBA and structural firefighter's uniform may provide limited protection.
Flash Point	67 °C [Closed cup]
Lower Explosion Limit	1.1 %
Upper Explosion Limit	10.6 %
Auto Ignition Temperature	230 - 245 °C
Hazchem Code	No Data Available

6. ACCIDENTAL RELEASE MEASURES

General Response Procedure	Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames). Do not touch or walk through spilled material. Avoid breathing vapours and contact with eyes, skin and clothing.
Clean Up Procedures	Absorb with earth, sand or other non-combustible material and transfer to a suitable container for disposal (see SECTION 13). Use non-sparking tools. For large amounts: Pump off product. *Use clean non-sparking tools to collect absorbed material.
Containment	Stop leak if safe to do so – Prevent entry into waterways, drains or confined areas.
Decontamination	Wash away remainder with plenty of water.
Environmental Precautionary Measures	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. Local authorities should be advised if significant spillages cannot be contained.
Evacuation Criteria	Spill or leak area should be isolated immediately. Keep unnecessary and unprotected personnel from entering the area. Large spills: Dike area to contain spill.
Personal Precautionary Measures	Use personal protective equipment as required (see SECTION 8).

7. HANDLING AND STORAGE

Handling	Safety showers and eyewash facilities should be provided within the immediate work area for emergency use. Ensure adequate ventilation - Use only outdoors or in a well-ventilated area. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing mist/vapours/spray and contact with eyes, skin and clothing. Do not ingest. Wear protective gloves/protective clothing/eye protection/face protection (see SECTION 8). Combustible liquid: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Ground and bond container and receiving equipment. Electrical installations/working materials must comply with the technological safety standards.
Storage	Store in a cool, dry and well-ventilated place, out of direct sunlight. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Keep away from foodstuffs and incompatible materials (see SECTION 10). Store locked up.
Container	Keep in the original container or store in the following material(s): Carbon steel, Stainless steel, Phenolic lined steel drums. Do not store in Aluminum, Copper, Galvanized iron, Galvanized steel. *Containers, even those that have been emptied, can contain vapours. Do not cut, drill, grind, weld or perform similar operations on or near empty containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

General	For SUBSTANCE: 2-Butoxyethanol (CAS No. 111-76-2): - Safe Work Australia Exposure Standard: TWA = 20 ppm (96.9 mg/m3); STEL = 50 ppm (242 mg/m3); Absorption through the skin may be a significant source of exposure (Sk).
----------------	--

Safety Data Sheet, Butyl glycol, Revision 4, 14/02/2023

- New Zealand Workplace Exposure Standard [Next review 2023]: TWA = 25 ppm (121 mg/m³); Skin absorption (skin).
- NIOSH REL: TWA = 5 ppm (24 mg/m³).
- OSHA PEL: TWA = 50 ppm (240 mg/m³).
- Immediately Dangerous to Life or Health (IDLH) Concentration: 700 ppm.

Exposure Limits

No Data Available

Biological Limits

No information available.

Engineering Measures

A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area.

Personal Protection Equipment

- Respiratory protection: Wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. Recommended: use an approved air-purifying respirator, Organic vapour cartridge (refer to AS/NZS 1715 & 1716).
 - Eye/face protection: Wear appropriate eye protection to avoid eye contact. Recommended: Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.
 - Hand protection: Wear protective gloves. Recommended: Use chemical resistant gloves, e.g. Butyl rubber, Ethyl vinyl alcohol laminate (EVAL).
 - Skin/body protection: Wear appropriate personal protective clothing to avoid skin contact. Recommended: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.
- *Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.

Special Hazards Precautions

Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

Work Hygienic Practices

Do not eat, drink or smoke when using this product. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Appearance	Liquid
Odour	Mild; Ether-like
Colour	Colourless
pH	No Data Available
Vapour Pressure	0.87 mmHg (@ 20 °C)
Relative Vapour Density	4.1 Air = 1
Boiling Point	171 °C
Melting Point	No Data Available
Freezing Point	-75 °C
Solubility	>1,000 g/L in water 20°C [Literature]
Specific Gravity	0.9005 - 0.9040 (Water = 1)
Flash Point	67 °C [Closed cup]
Auto Ignition Temp	230 - 245 °C
Evaporation Rate	0.06 (Butyl acetate = 1)
Bulk Density	No Data Available
Corrosion Rate	No Data Available
Decomposition Temperature	No Data Available
Density	0.902 g/cm ³ Liquid density [Literature]
Specific Heat	No Data Available
Molecular Weight	118.2 g/mol
Net Propellant Weight	No Data Available
Octanol Water Coefficient	log Pow: 0.81 (20 °C)
Particle Size	No Data Available
Partition Coefficient	No Data Available

Saturated Vapour Concentration	No Data Available
Vapour Temperature	No Data Available
Viscosity	Dynamic: 3.3 mPa.s - Kinematic: 3.7 mm ² /s (@ 20 °C)
Volatile Percent	No Data Available
VOC Volume	No Data Available
Additional Characteristics	No information available.
Potential for Dust Explosion	Not applicable.
Fast or Intensely Burning Characteristics	No information available.
Flame Propagation or Burning Rate of Solid Materials	No information available.
Non-Flammables That Could Contribute Unusual Hazards to a Fire	Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.
Properties That May Initiate or Contribute to Fire Intensity	Combustible liquid; May burn but does not ignite readily.
Reactions That Release Gases or Vapours	During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include Carbon oxides.
Release of Invisible Flammable Vapours and Gases	No information available.

10. STABILITY AND REACTIVITY

General Information	Product can oxidize at elevated temperatures. May form peroxides in the presence of air. Generation of gas during decomposition can cause pressure in closed systems.
Chemical Stability	Thermally stable at typical use temperatures.
Conditions to Avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not distill to dryness.
Materials to Avoid	Incompatible/reactive with strong acids, strong oxidizers, Bases, Amines, Ammonia, Acid chlorides.
Hazardous Decomposition Products	Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include Aldehydes, Ketones, Organic acids.
Hazardous Polymerisation	Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

General Information	<ul style="list-style-type: none"> - Acute toxicity: Harmful if swallowed, in contact with skin and if inhaled. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Massive ingestion of ethylene glycol monobutyl ether (attempted suicides) may produce metabolic acidosis and subsequent secondary effects such as hemolysis, central nervous system and kidney effects. - Skin corrosion/irritation: Causes skin irritation. Brief contact may cause slight skin irritation with local redness. Repeated exposure may cause irritation, even a burn. May cause more severe response on covered skin (under clothing, gloves). - Eye damage/irritation: Causes serious eye irritation. May cause moderate corneal injury. Effects may be slow to heal. Vapour may cause eye irritation experienced as mild discomfort and redness. - Respiratory/skin sensitisation: Did not cause allergic skin reactions when tested in humans. Did not cause allergic skin reactions when tested in guinea pigs. - Germ cell mutagenicity: In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were negative. - Carcinogenicity: In long-term animal studies with ethylene glycol butyl ether, small but statistically significant increases in tumors were observed in mice but not rats. The effects are not believed to be relevant to humans. If the material is handled in accordance with proper industrial handling procedures, exposures should not pose a carcinogenic risk to man. - Reproductive toxicity: In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals. - STOT (single exposure): May cause respiratory irritation. Excessive exposure may cause irritation to upper respiratory tract (nose and throat). In humans, symptoms may include Headache. In animals, effects have been reported on the blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits.
----------------------------	--

Safety Data Sheet, Butyl glycol, Revision 4, 14/02/2023

- STOT (repeated exposure): Results from acute and repeat exposure studies in rats, mice and rabbits indicate that EGBE causes injury to red blood cells with subsequent intravascular hemolysis and anemia, and secondary changes in the liver and kidney. Human and guinea pig red blood cells are resistant to EGBE injury and therefore the effects noted in sensitive species are not relevant to humans.
- Aspiration toxicity: Based on physical properties, not likely to be an aspiration hazard.

Acute

Ingestion	Acute toxicity (Oral): - LD50, Rat: 1,300 mg/kg
Other	Acute toxicity (Dermal): - LD50, Guinea pig: >2,000 mg/kg
Inhalation	Acute toxicity (Inhalation): - LC0, Guinea pig: >3.1 mg/l (1 h); No deaths occurred at this concentration.
Carcinogen Category	None

12. ECOLOGICAL INFORMATION

Ecotoxicity	Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
Persistence/Degradability	Material is readily biodegradable (90.4 %, 28 days) [OECD Test Guideline 301B or Equivalent].
Mobility	Potential for mobility in soil is high (Koc between 50 and 150). - Koc: 67 [Estimated].
Environmental Fate	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.
Bioaccumulation Potential	Bioconcentration potential is low (BCF < 100 or Log Pow < 3). - log Pow: 0.81 [Measured]. - BCF: 3.2
Environmental Impact	No Data Available

13. DISPOSAL CONSIDERATIONS

General Information	Where reuse or recycling are not appropriate, dispose of the product in an environmentally sound manner in accordance with relevant Commonwealth, state, territory and local government legislation.
Special Precautions for Land Fill	For unused and uncontaminated product, the preferred options include sending to a licensed, permitted incinerator or other thermal destructive device.

14. TRANSPORT INFORMATION

Land Transport (Australia)

ADG Code

Proper Shipping Name	ETHYL GLYCOL MONOBUTYL ETHER
Class	C1 Combustible Liquids - Flash Point >60°C - <=93°C, Closed Cup
Subsidiary Risk(s)	No Data Available No Data Available
UN Number	No Data Available
Hazchem	No Data Available
Pack Group	No Data Available
Special Provision	No Data Available
Comments	NON-DANGEROUS GOODS: Not regulated for LAND transport.

Land Transport (Malaysia)

ADR Code

Proper Shipping Name	ETHYL GLYCOL MONOBUTYL ETHER
Class	No Data Available
Subsidiary Risk(s)	No Data Available
	No Data Available
UN Number	No Data Available
Hazchem	No Data Available
Pack Group	No Data Available
Special Provision	No Data Available
Comments	NON-DANGEROUS GOODS: Not regulated for LAND transport.

Land Transport (New Zealand)

NZS5433

Proper Shipping Name	ETHYL GLYCOL MONOBUTYL ETHER
Class	No Data Available
Subsidiary Risk(s)	No Data Available
	No Data Available
UN Number	No Data Available
Hazchem	No Data Available
Pack Group	No Data Available
Special Provision	No Data Available
Comments	NON-DANGEROUS GOODS: Not regulated for LAND transport.

Land Transport (Thailand)

Proper Shipping Name	ETHYL GLYCOL MONOBUTYL ETHER
Class	No Data Available
Subsidiary Risk(s)	No Data Available
	No Data Available
UN Number	No Data Available
Hazchem	No Data Available
Pack Group	No Data Available
Special Provision	No Data Available
Comments	NON-DANGEROUS GOODS: Not regulated for LAND transport.

Land Transport (United States of America)

US DOT

Proper Shipping Name	ETHYL GLYCOL MONOBUTYL ETHER
Class	No Data Available
Subsidiary Risk(s)	No Data Available
	No Data Available
UN Number	No Data Available
Hazchem	No Data Available
Pack Group	No Data Available
Special Provision	NA1993
Comments	49 CFR § 173.150: Not regulated if shipped in non-bulk packages less than or equal to 119 gallons (450 litres).

Sea Transport

IMDG Code

Proper Shipping Name	ETHYL GLYCOL MONOBUTYL ETHER
Class	No Data Available
Subsidiary Risk(s)	No Data Available
UN Number	No Data Available
Hazchem	No Data Available
Pack Group	No Data Available
Special Provision	No Data Available
EMS	No Data Available
Marine Pollutant	No
Comments	NON-DANGEROUS GOODS: Not regulated for SEA transport.

Air Transport

IATA DGR

Proper Shipping Name	ETHYL GLYCOL MONOBUTYL ETHER
Class	No Data Available
Subsidiary Risk(s)	No Data Available
UN Number	No Data Available
Hazchem	No Data Available
Pack Group	No Data Available
Special Provision	No Data Available
Comments	NON-DANGEROUS GOODS: Not regulated for AIR transport.

National Transport Commission (Australia)

Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)

Dangerous Goods Classification	NOT Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road & Rail (ADG Code)
---------------------------------------	---

15. REGULATORY INFORMATION

General Information	No Data Available
Poisons Schedule (Aust)	Schedule 6

Environmental Protection Authority (New Zealand)

Hazardous Substances and New Organisms Amendment Act 2015

Approval Code	HSR001154
----------------------	-----------

National/Regional Inventories

Australia (AIC)	Listed
Canada (DSL)	Not Determined
Canada (NDSL)	Not Determined

China (IECSC)	Not Determined
Europe (EINECS)	Not Determined
Europe (REACH)	Not Determined
Japan (ENCS/METI)	Not Determined
Korea (KECI)	KE-04134
Malaysia (EHS Register)	Not Determined
New Zealand (NZIoC)	Listed
Philippines (PICCS)	Not Determined
Switzerland (Giftliste 1)	Not Determined
Switzerland (Inventory of Notified Substances)	Not Determined
Taiwan (NCSR)	Not Determined
USA (TSCA)	Listed

16. OTHER INFORMATION

Related Product Codes

ETGLBE0100, ETGLBE0500, ETGLBE0800, ETGLBE0900, ETGLBE1000, ETGLBE1001, ETGLBE1002, ETGLBE1003, ETGLBE1004, ETGLBE1005, ETGLBE1006, ETGLBE1007, ETGLBE1008, ETGLBE1009, ETGLBE1010, ETGLBE1011, ETGLBE1012, ETGLBE1013, ETGLBE1014, ETGLBE1015, ETGLBE1016, ETGLBE1017, ETGLBE1018, ETGLBE1019, ETGLBE1050, ETGLBE1051, ETGLBE1054, ETGLBE1055, ETGLBE1056, ETGLBE1057, ETGLBE1058, ETGLBE1100, ETGLBE1300, ETGLBE1500, ETGLBE1501, ETGLBE1700, ETGLBE1801, ETGLBE1802, ETGLBE1803, ETGLBE1804, ETGLBE1805, ETGLBE1806, ETGLBE1807, ETGLBE1808, ETGLBE1809, ETGLBE1810, ETGLBE1811, ETGLBE1812, ETGLBE1813, ETGLBE1814, ETGLBE1815, ETGLBE1816, ETGLBE1817, ETGLBE1818, ETGLBE1819, ETGLBE1820, ETGLBE2000, ETGLBE2001, ETGLBE2200, ETGLBE2300, ETGLBE2310, ETGLBE2400, ETGLBE2500, ETGLBE2600, ETGLBE2704, ETGLBE2804, ETGLBE2805, ETGLBE2807, ETGLBE2820, ETGLBE3000, ETGLBE3001, ETGLBE3002, ETGLBE3003, ETGLBE3010, ETGLBE3011, ETGLBE3020, ETGLBE3021, ETGLBE3022, ETGLBE3023, ETGLBE3030, ETGLBE3031, ETGLBE3032, ETGLBE3040, ETGLBE3301, ETGLBE3400, ETGLBE3500, ETGLBE4000, ETGLBE4200, ETGLBE4201, ETGLBE4299, ETGLBE4500, ETGLBE4501, ETGLBE4502, ETGLBE4600, ETGLBE5000, ETGLBE5200, ETGLBE5500, ETGLBE5700, ETGLBE5900, ETGLBE6000, ETGLBE6001, ETGLBE6002, ETGLBE6300, ETGLBE6500, ETGLBE6600, ETGLBE6800, ETGLBE6910, ETGLBE6912, ETGLBE6920, ETGLBE6926, ETGLBE6930, ETGLBE6931, ETGLBE6935, ETGLBE6936, ETGLBE6938, ETGLBE6939, ETGLBE6940, ETGLBE6942, ETGLBE6960, ETGLBE7000, ETGLBE7200, ETGLBE7203, ETGLBE7500, ETGLBE8000, ETGLBE8001, ETGLBE8002, ETGLBE8015, ETGLBE8016, ETGLBE8017, ETGLBE8018, ETGLBE8500, ETGLBE8800, ETGLBE8805, ETGLBE9000, ETGLBE9010, ETGLBE9100, ETGLBE9300, ETGLBE9301, ETGLBE9500, ETGLBE9800, ETGLBE9900, ETGLBE9901, ETGLBE9902, ETGLBE9915, ETGLBE9916

Revision

4

Revision Date

14/02/2023

Key/Legend

< Less Than

> Greater Than

AICS Australian Inventory of Chemical Substances

atm Atmosphere

CAS Chemical Abstracts Service (Registry Number)

cm² Square Centimetres

CO₂ Carbon Dioxide

COD Chemical Oxygen Demand

deg C (°C) Degrees Celcius

EPA (New Zealand) Environmental Protection Authority of New Zealand

deg F (°F) Degrees Farenheit

g Grams

g/cm³ Grams per Cubic Centimetre

g/l Grams per Litre

HSNO Hazardous Substance and New Organism

IDLH Immediately Dangerous to Life and Health

Safety Data Sheet, Butyl glycol, Revision 4, 14/02/2023

immiscible Liquids are insoluble in each other.

inHg Inch of Mercury

inH₂O Inch of Water

K Kelvin

kg Kilogram

kg/m³ Kilograms per Cubic Metre

lb Pound

LC₅₀ LC stands for lethal concentration. LC₅₀ is the concentration of a material in air which causes the death of 50% (one half) of a group of test animals. The material is inhaled over a set period of time, usually 1 or 4 hours.

LD₅₀ LD stands for Lethal Dose. LD₅₀ is the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals.

ltr or **L** Litre

m³ Cubic Metre

mbar Millibar

mg Milligram

mg/24H Milligrams per 24 Hours

mg/kg Milligrams per Kilogram

mg/m³ Milligrams per Cubic Metre

Misc or **Miscible** Liquids form one homogeneous liquid phase regardless of the amount of either component present.

mm Millimetre

mmH₂O Millimetres of Water

mPa.s Millipascals per Second

N/A Not Applicable

NIOSH National Institute for Occupational Safety and Health

NOHSC National Occupational Health and Safety Commission

OECD Organisation for Economic Co-operation and Development

Oz Ounce

PEL Permissible Exposure Limit

Pa Pascal

ppb Parts per Billion

ppm Parts per Million

ppm/2h Parts per Million per 2 Hours

ppm/6h Parts per Million per 6 Hours

psi Pounds per Square Inch

R Rankine

RCP Reciprocal Calculation Procedure

STEL Short Term Exposure Limit

TLV Threshold Limit Value

tne Tonne

TWA Time Weighted Average

ug/24H Micrograms per 24 Hours

UN United Nations

wt Weight